



IRIICHI (MALAYSIA) SDN. BHD. (Company No. 177418-A)
Plot 507, Tingkat Perusahaan Empat, Kawasan Perusahaan Bebas Prai,
13600 Prai, Penang. Malaysia
Tel.: 604-3999801/2/3 Fax: 604-3992443

T- ECO Low Cost 4 Feet Tube Light

High Efficiency, Green Environment LED Tube Light

FEATURES

- Special Low cost version
- Simple designed LED Tube Light
- High light emission and less heat generation
- Up to 50% savings on energy used
- Effective lighting distribution
- Mercury and UV can be replaced

APPLICATION

- Parking bays
- Supermarkets
- Shopping complex
- Home and offices
- Hospitals
- Hotels



SPECIFICATION

ITEM		LSBL-40PIL-A
Type		40W
Luminous Flux (lm)		1750
Illumination	1m (lx)	300
	2m (lx)	86
View Angle (1/2 Beam Angle)		170°
Color Temperature CCT K		6500K
Color Rendering Index (CRI)		Ra 85%
Socket		G13
T9 Tube	Size (mm)	1,198 x ϕ 30
	Weight (g)	400
Operating Voltage		Voltage: AC220~240V Frequency: 50/60Hz
Power Consumption (W)		16
LED Life Span		50,000 hours
Operating Environment		Temperature: -20~50°C Humidity: 5~95%